



Neutralysal Premium

Version: feb-17

Neutralysal Premium is a colourless saltpetre resistant treatment. It acts as a salt sequestering agent and prevents the appearance of white stains brought caused by salinity.

PRODUCT DESCRIPTION

Where to apply:

Ideal for preventing and curing façades and exterior and interior walls that have been degraded by saltpetre.

Features:

Protects from effects of saltpetre.
Prevents the appearance of white stains.
Suitable for interiors and exteriors.
High resistance and durability.
Does not peel.

Technical properties:

Specific weight	1.2 ± 0.05 g/cm ³
pH	12.5 ± 1
Viscosity	< 50 K.U.
Nature	EDTA.Na ₄
Appearance	Yellowish liquid
Finish	Colourless

Yield:

Coverage depends on the type, texture and absorption of the substrate. As an estimate, we consider 7-8 m²/l.

Format:

Available in pots of 1 l y 5 l. Inquire about other formats.

Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun expo-

sure. Unopened, it may be conserved for at least 12 months.

APPLICATION INSTRUCTIONS

Conditions of the substrate:

The support must be dry, firm, well adhered and free from any impurities that may hinder the product's penetration.

Preparation of the substrate:

Clean the substrate with water to force the precipitation of encapsulated sales. Wait at least 48 hours before applying.

Should there be colonies of mould, lichens, algae and bacteria, brush with sodium hypochlorite (bleach).

If outer layers are deteriorated, remove them until you reach a clean substrate.

If the substrate contains pathologies such as moisture due to capillarity, condensation, leak, biodeterioration or movements of the substrate, etc., then it is necessary to resolve the structural problems first.

Application method:

Mix well to ensure an even consistency and apply one coat evenly.

Drying:

In conditions of 25 °C and 60% relative humidity, allow 24 hours for drying.

Environmental conditions:



The work temperature (environment and substrate) must be greater than +5 °C and less than +32 °C. Do not apply in direct sunlight, nor on support heated by the sun.

Tools:

Roller, brush or spray gun.

Tool cleaning:

Clean tools after use with warm water.

Notes:

The indicated times are for environmental conditions of 25 °C and 60% relative humidity.

The mineral substrate must be at least 28 days old.

The substrates to be painted must be resistant to high alkalinity.

In case of rain, let the substrate dry for at least 48 hours before applying.

It is recommended to protect the treated surface from rain until application of the coating.

Avoid contact with aluminum, copper, copper and nickel alloys.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Do not mix with other products or specific properties may change.

According to local legal provisions. The packages are made of recycled polypropylene.

Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Technical substrate:

For further information, please contact your local distributor or manufacture:

technicalsupport@graphenstone.com.

ADDITIONAL INFORMATION

Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste management:

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and

Graphenstone Spain | Polg Ind Poliviso. C/Carpinteros, 25. EL VISO DEL ALCOR, 41520 Sevilla, España.. Tel.: +34 955 292 068





verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.

